

ZDWE系列精密行星减速机

ZDWE SERIES PRECISIOM PLANETARY GEAR MOTOR

产品图 Product Graph

技术资料 Technical Data

产品型号 Product type		60	80	120	160	减速比 Reduction ratio	级数 Number of stage
额定输出扭矩 Rated output torque	N.M	12	40	80	400	3	1
		16	50	110	450	4	
		16	50	110	450	5	
		15	45	100	400	8	
		12	40	80	305	10	
		40	100	210	/	9	2
		40	100	210	700	12	
		40	100	210	700	15	
		44	120	260	800	16	
		44	120	260	800	20	
		40	110	230	700	25	
		44	120	260	800	32	
		40	110	230	700	40	
		18	45	100	400	64	
		40	100	210	/	60	3
		44	120	260	/	80	
		44	120	260	/	100	
		40	100	210	/	120	
		44	120	260	/	160	
		40	110	230	/	200	
		44	120	260	/	256	
		40	110	230	/	320	
		18	45	100	/	512	
寿命 Life	小时 Hour	20,000					
瞬间急停扭矩 Instant stop torque	N.M	2倍于额定输出扭矩 Two times of rated output torque					
产品型号 Product type		60	80	120	160	单位 Unit	级数 Number of stage
最大径向力 Max radial torque		450	900	2100	6000	N	
最大轴向力 Max axial torque		225	450	1050	3000	N	
满载效率 Full load efficiency		94				%	1
		92					2
		88					3
重量 Weight		1.7	4.4	12	36	Kg	1
		1.9	5	14	40		2
		2.1	5.5	16	/		3
工作温度 Operating temperature		-25~+90				℃	
保护等级 IP		IP54					
润滑方式 Lubrication type		终身润滑 Lifetime lubrication					
安装方式 Mounting type		任意 Any					

最大径向力与最大轴向力,输出100RPM时,作用于输出轴中心位置(L/2)处。
The max radial and axial torque work in the location of the center of output shaft when the out speed is 100RPM.

ZDWE系列精密行星减速机

ZDWE SERIES PRECISIOM PLANETARY GEAR MOTOR

■ 技术资料 Technical Data

产品型号 Product type		60	80	120	160	减速比 Reduction ratio
转动惯量 Moment of inertia	Kgcm ²	0.246	1.189	5.75	24.5	3
		0.204	0.939	3.91	19.4	4
		0.189	0.869	3.35	17.5	5
		0.176	0.809	2.89	15.9	8
		0.152	0.730	2.54	15.5	10
		0.242	1.159	5.73	/	9
		0.199	0.919	3.83	/	12
		0.188	0.859	3.28	17.5	15
		0.199	0.919	3.83	19.4	16
		0.186	0.859	3.28	17.5	20
		0.186	0.859	3.26	17.5	25
		0.175	0.809	2.84	15.9	32
		0.175	0.809	2.84	15.9	40
		0.175	0.809	2.84	15.9	64
		0.186	0.919	3.28	/	60
		0.186	0.919	3.28	/	80
		0.186	0.859	3.26	/	100
		0.175	0.809	2.84	/	120
		0.175	0.809	2.84	/	160
		0.175	0.809	2.84	/	200
		0.175	0.809	2.84	/	256
		0.175	0.809	2.84	/	320
		0.175	0.809	2.84	/	512


产品型号 Product type		60	80	120	160	级数 Number of stage
回程间隙 Backlash	arcmin 弧分	< 30	< 25	< 25	< 25	1
		< 35	< 30	< 30	< 30	2
		< 40	< 35	< 35	/	3
抗扭刚性 Torsional stiffness	N.M/arcmin	1.5	4.5	10	38	1
		2.5	6.5	13	43	2
		2.5	6.3	12	/	3
噪声 Noise	dB(A)	65	68	70	70	
最高输入转速 Max input speed	min ⁻¹	4500	4500	4500	4500	
推荐输入转速 Recommnd input speed	min ⁻¹	3000	3000	3000	3000	

1. 转动惯量与输入轴有关。The moment of inertia is related with input shaft.
2. 噪声检测标准，距离1m，在输入转速3000转/分空载时测得。Noise test standard pressure level, distance 1m, measured on idle running with an input speed of 3000rpm.

ZDWE系列精密行星减速机

ZDWE SERIES PRECISIOM PLANETARY GEAR MOTOR

机械参数 Dimensions




单位 Unit: mm

产品型号 Product type	60ZDWE			80ZDWE			120ZDWE			160ZDWE	
级数 Number of stage	1	2	3	1	2	3	1	2	3	1	2
L1箱体总长 L1 overall length	150	163	176	184.5	202.5	220	249.2	277	304.5	380	423.5
L3箱体长度 L3 body length	46.5	59.5	72.5	60	78	95.5	73.7	101.5	129	141	184.5
L12总高 L12 overall hights	93			119.5			167.5			229	
输出端 Output											
L4出轴长度 L4 output shaft length	35			40			55			87	
L5出轴长至轴肩 L5 output length to the shaft shoulder	30.5			36			50			80	
L6键长度 L6 key length	25			28			40			70	
L7键至轴末端长 L7 key length to the shaft end	2.5			4			5			5	
L8定位凸台长度 L8 spigot length	3			3			4			5	
D4出轴直径 D4 output shaft diameter	Φ14h7			Φ20h7			Φ25h7			Φ40h7	
D5轴肩直径 D5 shaft shoulder diameter	Φ17			Φ25			Φ35			Φ55	
D6定位凸台直径 D6 spigot diameter	Φ40h7			Φ60h7			Φ80h7			Φ130h7	
D7箱体直径 D7 body diameter	Φ60			Φ80			Φ115			Φ160	
D8安装孔分布圆 D8 hole circle	Φ52			Φ70			Φ100			Φ145	
B1键宽 B1 key width	5			6			8			12	
H1键高 H1 key height	16			22.5			28			43	
G2安装螺纹孔x深度 G2 mounting thread x depth	M5X8			M6X10			M10X16			M12X20	
G3中心螺纹孔 G3 center screw hole	M5X12			M6X16			M10X22			M12X25	
输入端 Input											
L2输入法兰长度 L2 input flange length	20			32			38			66	
L9电机轴长度 L9 motor shaft length	30			40			58			81	
L10定位凸台深 L10 spigot depth	5			10			10			10	
D1安装孔分布圆 D1 mounting hole distribution circle	Φ70			Φ90			Φ145			Φ200	
D2定位凸台直径 D2 spigot diameter	Φ50G7			Φ70G7			Φ110G7			Φ114.3G7	
D3输入轴轴径 D3 input shaft diameter	≤Φ14G7			≤Φ19G7			≤Φ24G7			≤Φ35G7	
G1安装螺纹孔x深度 G1 mounting threads x depth	M5X12			M6X15			M8X22			M12X25	
Q3输入法兰 Q3 input flange	□60			□80			□130			□175	

※输入端尺寸可根据电机尺寸制作。
 ※Input size made according to motor size.

伺服电机对应尺寸表 SERVO MOTOR CORRESPONDING SIZE TABLE

减速器输入端 Gearbox Input



输入法兰与伺服电机对应尺寸表 Input Flange And Servo Motor Matching Table

电机功率 Motor Power (W)	电机尺寸 Motor Size	安装距 Installation Distance	螺纹孔 Threaded Hole	边框 Frame	孔径 Aperture	止口 Stop	止口深度 Stop Depth	轴伸 Shaft Extension
		A	B	C	D	E	F	I
50	T1	45	M3	38	8	30	3	25
	T2	46	M4	40	6	30	3	25
	T3	47	M4	40	8	30	3	25
	T4	48	M3	42	8	30	3	25
100	T1	45	M3	38	8	30	3	25
	T2	46	M4	40	8	30	3	25
	T3	46	M4	40	8	30	3	25
	T4	48	M3	42	8	30	3	25
200	T1	70	M4	60	11	50	3	30
	T2	70	M5	60	14	50	3	30
	T3	70	M5	60	14	50	3	30
400	T1	70	M4	60	14	50	3	30
	T2	70	M5	60	14	50	3	30
	T3	70	M5	60	14	50	3	30
750	T1	90	M5	80	19	70	3	35
	T2	90	M6	80	16	70	3	40
	T3	90	M6	80	19	70	3	40
	T4	100	M6	86	16	80	3	35
	T5	145	M8	130	19	110	6	58
	T6	100	M6	86	19	80	3	40
1000	T1	100	M6	90	19	80	3	55
	T2	115	M6	100	24	95	3	45
	T3	115	M8	100	24	95	5	45
	T4	145	M8	130	22	110	6	58
	T5	145	M8	130	22	110	6	70
	T6	115	M8	100	22	95	5	45
	T7	145	M8	130	24	110	3	55
1500	T1	115	M8	100	19	95	3	55
	T2	115	M6	100	24	95	3	45
	T3	115	M8	100	24	95	3	45
	T4	145	M8	130	22	110	6	58
	T5	145	M8	130	22	110	6	70
	T6	115	M8	100	22	95	5	45
	T7	145	M8	130	24	110	3	55

伺服电机对应尺寸表

SERVO MOTOR CORRESPONDING SIZE TABLE

输入法兰与伺服电机对应尺寸表 Input Flange And Servo Motor Matching Table

电机功率 Motor Power (W)	电机尺寸 Motor Size	安装距 Installation Distance	螺纹孔 Threaded Hole	边框 Frame	孔径 Aperture	止口 Stop	止口深度 Stop Depth	轴伸 Shaft Extension
		A	B	C	D	E	F	I
2000	T1	115	M8	100	19	95	3	55
	T2	115	M6	100	24	95	3	45
	T3	115	M8	100	24	95	3	45
	T4	145	M8	130	22	110	6	58
	T5	200	M12	130	35	114.3	10	80
	T6	115	M8	100	22	95	5	45
2500	T1	115	M8	100	19	95	3	55
	T2	115	M6	100	24	95	3	45
3000	T1	130	M8	120	22	110	3	55
	T2	145	M8	130	28	110	6	65
	T4	145	M8	130	24	110	6	65
	T5	200	M12	175	35	114.3	10	80
	T7	200	M12	175	35	114.3	10	65
3500	T1	130	M8	120	22	110	3	55
	T2	145	M8	130	28	110	3	63
	T5	200	M12	175	35	114.3	10	80
4000	T1	145	M8	130	24	110	6	65
	T2	145	M8	130	28	110	6	65
	T5	200	M12	175	35	114.3	10	80
	T6	200	M12	175	42	114.3	10	113
4500	T1	145	M8	130	24	110	6	65
	T5	200	M12	175	35	114.3	10	80
	T6	200	M12	175	42	114.3	10	113
	T7	200	M12	175	35	114.3	10	65
5000	T1	145	M8	130	24	110	6	65
	T2	145	M8	130	28	110	6	65
	T5	200	M12	175	35	114.3	10	80
	T7	200	M12	175	35	114.3	10	65

注1)没有油封和尺寸不同时，安装带油封的马达有时需特别订货。
If an oil-seal is not present and the size is different, attachment of the oil-seal may correspond to special order, in some cases.

注2)马达轴为D形轴、锥形时需要特别订货。
If the motor shaft is of D-cut and taper type, it corresponds to a special order.

注3)标准外有时需要特别订货。欲知详情，请另外与本公司联系。
Out-of-standard may correspond to a special order in some cases, For details, contact us.